

SPANLOAD

...SAFETY FIRST

POLYESTER

EYE - EYE SLINGS

HIJSBANDEN MET LUSSEN

SCHLAUFEN HEBEBÄNDER



BEARS YOUR BUSINESS

SPANLOAD

...SAFETY FIRST



Polyester Slings since 2007.

Spanload stands for Safety & Efficiency. Standardized for volume handlings. Tailor made for heavy projects cargo... always at the top of the quality standards.

SPANLOAD...Safety First | Bears your Business

BEARS YOUR BUSINESS

NEN

EN1492-1 | EN1492-2



- Highest safety for your workers.
- Long durability | Reusable.
- Consistent quality | highest standards.
- 100% compliant to EN 1492.
- At the top of the quality standards.
- Always with Safety Factor 7:1.
- Production according to ISO 9001
- Inspection certificate for each production batch.
- Any length as per customer request.
- Customer name print on Spanload slings possible.
- Standardized sizes available from stock.

Typical: Lifting slings for general purpose use | Safety Factor 7:1



Products according to:

NEN

EN1492-1 | EN1492-2



CE

DIN

SPANLOAD

... SAFETY FIRST

"In the past we used slings from various suppliers but we did not always know who produced them. 3 years ago we decided to replace them by Spanload slings. Using one brand only which we can rely on for 100% makes me feel very comfortable, because now I know my workers are safe when handling our products"

... steel constructor from Belgium






"We handle various goods in our port and need tailor made lifting solutions for different cargos. Spanload offers all we need."

... port operator from The Netherlands



BEARS YOUR BUSINESS

Instruction for Spanload Sling Use

WORK LOAD LIMITS IN TONS						
WLL	COLOR	STRAIGHT LIFT	CHOKE LIFT	BASKET HITCH		
						
				PARALLEL	0 < 45 degrees	45 < 60 degrees
		M = 1	M = 0.8	M = 2	M = 1.4	M = 1
0.5 TON	WHITE	0.5	0.4	1.0	0.7	0.5
0.75 TON	WHITE	0.75	0.6	1.25	1.05	0.75
1 TON	VIOLET	1.0	0.8	2.0	1.4	1.0
1.5 TON	WHITE	1.5	1.2	3.0	2.1	1.5
2 TON	GREEN	2.0	1.6	4.0	2.8	2.0
3 TON	YELLOW	3.0	2.4	6.0	4.2	3.0
4 TON	GREY	4.0	3.2	8.0	5.6	4.0
5 TON	RED	5.0	4.0	10.0	7.0	5.0
6 TON	BROWN	6.0	4.8	12.0	8.4	6.0
8 TON	BLUE	8.0	6.4	16.0	11.2	8.0
10 TON	ORANGE	10.0	8.0	20.0	14.0	10.0

M = MODE FACTOR FOR SYMMETRICAL LOADING AND HANDLING TOLERANCE FOR SLINGS | EN1492-1



SPANLOAD

... SAFETY FIRST

IMPORTER | PRODUCER

Van Dijk Supplies
Phone: +31 (0) 26 4720368
Fax: +31 (0)26 4722741
Mail: info@spanload.com
Zipcode: 6666 ZG
Address: P.O. Box 20, Heteren

WWW.SPANLOAD.COM

BEARS YOUR BUSINESS

SPANLOAD product brochures:

- Polyester Sling Endless Flat | EN1492-1
- *Polyester Sling Eye-Eye* | EN1492-1
- Polyester Sling Endless Round | EN1492-2
- Polyester Ratches | EN12195-2

Products according to:



EN1492-1 | EN1492-2

